



GE APPLIANCES
a Haier company

AIR & WATER SOLUTIONS

RealMAX Ultra Low NOx Atmospheric Gas Water Heaters

KEY FEATURES

ULTRA LOW NOx BURNER

Low emissions, environmentally-friendly burner. Meets requirements for California and Utah residents.

REAL CAPACITY

Get the most from the only water heater offering that holds a true capacity of hot water compared to gas steel tank water heaters per DOE rated gallon capacity.

MAXIMUM PERFORMANCE

Live comfortably with this best-in-class water heater that delivers up to 83 gallons of hot water in the first hour of use measured through DOE First Hour Rating.

ANODE ROD

Durable magnesium design offers long-lasting protection against corrosion to extend the life of your water heater tank.

SMARTSHIELD™ SAFETY SYSTEM

Monitors the surrounding air and automatically shuts off the unit if abnormal temperatures are detected.

SELF-DIAGNOSTIC

Monitors and reports on gas system status via LED status indicator.

BRASS DRAIN VALVES

Rust-proof brass construction can be counted on to provide long-lasting service.

EASY INSTALLATION

Replace your old water heater quickly and easily using standard water, gas, and vent connections. T&P relief valve factory installed.

LEADING WARRANTY

RealMAX water heaters carry an 8-year or 10-year or 12-year tank and parts limited warranty.

SERVICEABILITY

RealMAX water heaters include a burner assembly alignment guide, high temp felt gasket and a resettable high temperature capability for easier and faster service. Additionally there are no filters that need cleaning.



Certified to
NSF/ANSI 372
See http://info.nsf.org/Certified/Lead_Content/
for specific model testing



Listed by
Underwriters
Laboratories



MADE IN
AMERICA
100% U.S. CONTENT | GEAPPLIANCES.COM/USA





Scan here to learn more about the full line of water heater solutions

Visit geappliancesairandwater.com for more details.

SPECIFICATION DETAILS

Model Number	Nominal Capacity (Gallons)	Rated Storage	First Hour Rating (Gallons) Est.	Uniform Energy Factor Min. Est.	Burner BTU Natural Gas Est.	Recovery 90° F Rise Gallon per Hour Est.	Vent Size	Drain Valve	Dimensions in Inches Approx.							Product Weight (lbs) est.	Shipping Weight (lbs) est.
									A	B	C	D	E	F	G		
Short Models																	
GG40S08DXV*	40	40	78	0.64	40,000	39	3" or 4"	Brass	52-1/4	48-7/8	22	11-1/4	8	41-1/4	50-3/8	135	142
GG50S08DXV*	50	50	77	0.63	40,000	42	3" or 4"	Brass	49-5/8	46-1/4	25	11-1/4	8	38	47-3/4	165	174
Tall Models																	
GG40T08DXV*	40	40	83	0.64	40,000	42	3" or 4"	Brass	61-7/8	58-1/2	20	11-1/4	8	51-3/8	60	142	149
GG50T08DXV*	50	50	82	0.64	40,000	42	3" or 4"	Brass	61-3/8	58	22	11-1/4	8	50-1/2	59-1/2	163	171

*Change 08 to 10 for 10-year warranty or 08 to 12 for 12-year tank and parts warranty.
 Water connections are 3/4".
 Gas connections are 1/2".
 Models approved for installation up to 10,100 feet from sea level.
 Dimensions and specifications are subject to change without notice.



Illustrations are intended for dimensional reference only. Refer to photograph for actual product appearance

INSTALLING THE WATER HEATER:

This water heater must be installed in accordance with these instructions, local codes, utility company requirements, and/or in the absence of local codes, the latest edition of the American National Standard/National Fuel Gas Code. A copy can be purchased from either the American Gas Association, 400 N. Capitol Street NW, Washington, DC 20001 as ANSI standard Z223.1 or National Fire Protection Association, 1 Batterymarch Park, Quincy, MA 02269 as booklet NFPA 54.

