

Hotpoint.

DUCTLESS HEAT PUMP

America's hardest working equipment.

Hotpoint® ductless mini-split systems deliver unmatched heating and cooling at an accessible price point. When pros choose Hotpoint® they're providing homeowners with best-in-class performance, nonstop comfort, and superior reliability — all backed by one of the toughest names in the industry.



ENVIRONMENTALLY COMPLIANT

All Hotpoint® systems use R-32 refrigerant, ensuring that they meet EPA Low GWP refrigerant regulations.*



WI-FI CONNECTIVITY

Hotpoint® systems connect seamlessly to the SmartHQ™ App from GE Appliances, giving homeowners more control over their comfort.



PROTECTIVE BASEPAN HEATER

A built-in basepan heater on outdoor units prevents systems from freezing, keeping systems operating at peak performance.



ALL-SEASON COMFORT

With heating down to -15°F and cooling up to 115°F, homeowners know they're coming home to comfort — no matter the weather outside.



EFFICIENT OPERATION

High-power turbo mode and warm start technology help heat and cool rooms more quickly, and an auto louver adjusts airflow upward when cooling and downward when heating.



HIGH-PERFORMANCE INVERTER TECHNOLOGY

A DC inverter compressor keeps indoor temperatures consistent in almost any climate and helps homeowners save money on energy.



FEDERAL & STATE INCENTIVES

Potential eligibility for federal and state incentives makes Hotpoint® the easy choice for price-conscious consumers.**



EASY TO INSTALL, EASY TO SERVICE

A mounting template and mounting plate with dimensions make installation a breeze, while an extended kickstand and easy-access control board let you service systems without removing casings. Plus, a two-way piping drain on the right and left sides makes installation easier and ensures units fit in more applications.



BUILT TO LAST

A hydrophilic aluminum fin helps prevent condensation buildup and ensures water flows through the unit smoothly.



WORRY-FREE WARRANTY

Unlock a 5-year limited parts and compressor warranty with registration.



GE APPLIANCES
a Haier company

AIR&WATER
SOLUTIONS

DUCTLESS HEAT PUMP

MODEL SPECIFICATIONS



	09K	12K	18K	24K
Model Number	Outdoor	1H09HN2DAB	1H12HN2DAB	1H18HN2DAB
	UPC	084691980575	084691980582	084691980599
	Indoor	HW09HN2DAB	HW12HN2DAB	HW18HN2DAB
	UPC	084691980612	084691980629	084691980636
Cooling	Capacity Range Btu/hr	3,100-11,000	3,300-13,800	4,100-20,000
	SEER2	18	18	18
	EER2	12	12	12
	Rated Capacity 95°F Btu/hr	9,000	12,000	18,000
Heating	Moisture Removal Pt/h	1.0	1.2	2.2
	Heating Capacity Range Btu/hr	2,100-11,000	2,800-13,300	3,800-20,000
	HSPF2 (IV)	9.5	9.5	9.5
	HSPF2 (V)	7.2	7.1	7.2
	Rated Heating Capacity 47°F Btu/hr	10,000	13,000	19,000
	Rated Heating Capacity 5°F Btu/hr	7,000	9,100	13,300
	Max. Heating Capacity 5°F Btu/hr	7,000	9,100	13,300
Operating Range	COP@5F	1.8	1.8	1.8
	Cooling °F (°C)	14-115°F (-10-46°C)	14-115°F (-10-46°C)	14-115°F (-10-46°C)
	Heating °F (°C)	-15-75°F (-26-24°C)	-15-75°F (-26-24°C)	-15-75°F (-26-24°C)
Power Supply	Voltage, Cycle, Phase V/Hz/-	208-230/60/1	208-230/60/1	208-230/60/1
	Compressor Type	DC Inverter Rotary	DC Inverter Rotary	DC Inverter Rotary
	Maximum Fuse Size A	15	15	20
	Minimum Circuit Amp A	12	12	14
	Basepan Heater	Yes	Yes	Yes
Outdoor Unit	Outdoor Noise Level dB	55	55	59
	Dimension: Height in (mm)	21 3/4 (553)	21 3/4 (553)	25 1/4 (642)
	Dimension: Width in (mm)	31 1/2 (800)	31 1/2 (800)	32 1/4 (820)
	Dimension: Depth in (mm)	11 (280)	11 (280)	12 (306)
	Weight (Net/Ship)- lbs (kg)	67.9/80.47 (30.8/36.5)	67.9/80.47 (30.8/36.5)	80.69/93.26 (36.6/42.3)
	Fan Speed Stages	5 + Auto	5 + Auto	5 + Auto
Indoor Unit	Maximum Indoor Sound Level (dB) (Turbo/High/Med/Low/Quiet)	45/43/38/32/28	46/44/39/33/29	49/46/43/40/31
	Dimension: Height in (mm)	11 (292)	11 (292)	12 1/8 (307)
	Dimension: Width in (mm)	31 3/4 (805)	31 3/4 (805)	34 1/2 (875)
	Dimension: Depth in (mm)	7 7/8 (200)	7 7/8 (200)	8 1/2 (217)
	Weight (Net/Ship)- lbs (kg)	18.74/24.47 (8.5/11.1)	18.74/24.47 (8.5/11.1)	21.83/28.22 (9.9/12.8)
Refrigerant Line	Refrigerant	R32	R32	R32
	Connections	Flare	Flare	Flare
	Liquid O.D. in	1/4	1/4	1/4
	Suction O.D. in	3/8	3/8	1/2
	Factory Charge Oz	25.8	25.8	38.8
	Maximum Line Length Ft (m)	66 (20)	66 (20)	83 (25)
	Line Length no additional charge needed Ft (m)	25 (7)	25 (7)	25 (7)
	Maximum Height Ft (m)	33 (10)	33 (10)	50 (15)

*Hotpoint models use R32 refrigerant. R32 is classified as a mildly flammable A2L refrigerant. At this time, some building codes restrict the use of products with A2L refrigerants in some applications. These restrictions vary by location. Refer to all local building codes for guidance on acceptable use of Low GWP (A2L) refrigerants for your application.

**All Hotpoint systems meet or exceed the 2025 CEE Split Air Source Heat Pump Specification and may qualify for the 2025 Energy Efficient Home Improvement Credit (25C). For further information, please visit www.cee1.org.

